

## 1 to 4 HDMI to single CAT6 splitter

Dear Customer

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

### Features:

- 1).Distributes 1 input HDMI signal to 4 identical UTP outputs, 4 outputs are synchronized.
- 2).Use single Cat5e/6 transmission distance up to 50m under 1080P@8-bit with 3D (the transmission distance for the receiver also need up to 50m)
- 3).Supports Resolutions up to 1080p@60Hz
- 4).Supports High Definition Audio: Dolby TrueHD, DTS-HD Master Audio
- 5).Supports 30/36bit deep color display.
- 6).Support 3D technology
- 7).DC 5V power

### NOTICE

Our company reserve the right to make changes in the hardware, packaging and any accompanying documentation without prior written notice.

Operating Instructions

### SPECIFICATIONS

- Operating Temperature Range -5 to +35°C(+23 to +95°F)  
Operating Humidity Range 5 to 90%RH (No Condensation)  
Video Amplifier Bandwidth 140MHz  
Input Video Signal 0.5-1.0 Volts P-P  
Input DDC Signal 5 volts p-p(TTL)  
Data transfer speed rate 6.75Gbps(Maximum)  
Video Format Supported VGA:640x480,800x600,1024x768,1080x1024  
DTV/HDTV:480i/576i/480P/576P/720P/1080i/1080P 3D video support  
Vertical Frequency range 60Hz  
Support Video Color Format xv-YCC/deep color 36bit  
Support Audio Format DTS-HD/true-HD/LPCM7.1/AC3/DTS/DSD  
Transmission Distance 1080P 8-bit 50m( If needed, HDMI extender is Optional )  
Over single cat5e or cat6 cable/24AWG/Solid  
Power consumption 12watts(Maximum)  
Dimension (L×W×H) L300xW155xH65mm  
Net Weight 490g

Note: Specifications are subject to change without notice. Mass and dimensions are approximate