# 4 Port DVI Switch 4 in 1 out support 1080p

# User Manual

## Introduction:

The 4-port DVI401 chart a revolutionary new direction in multimedia functionality by combining a Single Link DVI video switch. Now you can easily switch between the digital video and audio output of 4 digital devices (such as DVD players or computers), and enjoy it on a single DVI display and set of speakers.

### Feature:

1.Displays the video output of 4 digital devices (e.g.,DVD player, computer) on a single DVI display device

2.Fully compliant with DVI-Digital and DVI-Analog

3. Quick and easy switching via front panel pushbuttons or IR remote control

4.Superior video quality - up to 1920x1440.

5. Power On Detection – if one DVI source is powered off, the DVI201 will

automatically switch to the next powered-on source

6.Stackable design

7.Supports PCs and Macs

8.HDCP Compatible

### **Specifications:**

| Video Input  | Interface              | 4 x DVI-I Female (White)          |
|--------------|------------------------|-----------------------------------|
|              | Impedance              | 100 Ω                             |
|              | Max. Distance          | 1.8 m                             |
| Video Output | Interface              | 1 x DVI-I Female (White)          |
|              | Impedance              | 100 Ω                             |
|              | Max. Distance          | 5 m                               |
| Video        | Max. Data Rate         | 6.75 Gbps (2.25 Gbps Per<br>Lane) |
|              | Max. Pixel Clock       | 165 MHz                           |
|              | Compliance             | HDCP Compatible                   |
|              | Max. Resolution        | Up to 1920x1440                   |
|              | Max. Distance          | Up to 15 m                        |
| Power        | Connector: 1 x DC Jack |                                   |
|              | DC 5V,500mA            |                                   |
| Environment  | Operating Temp.        | 0 - 50°C                          |
|              | Storage Temp.          | -20 - 60°C                        |

|                     | Humidity   | 0-80% RH, Non-Condensing |
|---------------------|--|--------------------------|
| Housing             | Metal  |                          |
| Weight              | 0.800 kg   |                          |
| Dimensions          |  |                          |
| (L x W x H)         | 15*9*4 cm  |                          |
| package<br>contents | 1*User Manual,1*power adapter,1*IR remote control, 1*DVI<br>switch |                          |