

2 Port VGA Splitter 350MHZ

User Manual

Introduction:

2-Port VGA Splitter is VGA splitter that allow a single VGA video signal to be distributed to two output displays . The splitter support up to 350MHz video bandwidth, which provides optimum video quality, supported by resolutions up to 1920x1440.

The DK3502 is perfect for conference rooms, training facility & multi-display broadcasting, with cascable support up to three levels allowing a single video signal to be sent across up to 8 video displays while sustaining the highest quality possible.

Feature:

One video input to 2 video outputs

Superior video quality – up to 1920 x 1440 @ 60Hz

Supports up to 350MHz bandwidth for high performance video

Long distance transmission – up to 45m

Supports VGA, SVGA, UXGA, WUXGA, and multisync

Support EDID

Expandable – provides up to 2 video displays

Plug-and-play – no software installation required

Specification:

Video Input	Interface	1 x HDB-15 female (Blue)
	Impedance	75 Ω
	Max Distance	1.8 m
Video Output	Interface	2 x HDB-15 Female (Blue)
	Impedance	75Ω
Video	Max. Bandwidth	350 MHz
	Max. Resolutions	Up to 1920 x 1440
	Max Distance	Up to 45 m
EDID Settings	Port 1 / Auto / Default	
Power	Connector: 1 x DC Jack	
	Consumption: 9 V DC, 5W	
Environment	Operating Temp.	0-50°C
	Storage Temp.	-20 - 60°C
	Humidity	0-80% RH, Non-Condensing
Housing	Metal	

Weight	0.475 kg
Dimensions	13*9*4cm
(L x W x H)	
Carton Lot	40pcs